

LOCTITE®

55 PIPE SEALING CORD



- Allows fittings to be “backed-off” for alignment without fear of leakage
- Suitable for hot and cold water, potable water, gas, compressed air and industrial oils

ADJUSTABLE

FASTER

SAFER

EASIER

Henkel Technologies

LOCTITE®

A better joint for pipe systems

Loctite® 55 Pipe Sealing Cord is a new, faster, cleaner, more versatile pipe sealant which out-dates traditional tapes and hemp/paste combinations. It therefore enables the improvements required of today's pipe systems. Naturally, it complies with all latest regulations.

New technology, same traditional skills

You don't need special training to use Loctite® 55. Use your old skills to apply the new technology to get an instant seal. Wrap the sealing cord around the male threads, use the recommended number of turns for the size of thread - and assemble. That's all there is to a leak-proof joint.

4 easy steps....



....to a better joint

- **Loctite® 55**
replaces tapes, hemp and pastes
- **Loctite® 55**
seals pipe threads up to 4"
- **Loctite® 55**
has UK and European approvals for potable water and gas
- **Loctite® 55**
seals against hot or cold water, gas, compressed air, industrial and heating oils

- **Loctite® 55**
allows fittings to be "backed-off" for alignment without fear of leakage
- **Loctite® 55**
gives the bonus of speed, cleanliness and an assured first time seal that will not require return visits
- **Loctite® 55**
can be safely used on cast iron, steel, brass, copper, chrome, nickel-plated and galvanised surfaces, stainless steel and plastic parts

A single reel of Loctite 55 will seal:			
Thread size	1/2"	3/4"	1"
Approx. number of joints - 150 metre pack	385	260	180
Approx. number of joints - 50 metre pack	130	85	60



- **Loctite® 55**
is easily applied directly from these handy, pocket-sized, protective containers with a built-in cutter

Available in 150 and 50 metre packs

Henkel Loctite Adhesives Limited
Technologies House, Wood Lane End
Hemel Hempstead, Hertfordshire HP2 4RQ
Tel: 01442 418305 Fax: 01442 418228
E-mail: loctite@henkel.co.uk
Website: www.loctite.co.uk

Available from: